



P2031 HF LONGREACH 4.9M ANTENNA

**PACIFIC
AERIALS**

MOUNTS FOR P2031



MOUNTING KIT
P9055

TWIN P2031 WITH


P2034 VHF LongReach 4.9m
antenna

INSTALLATION

- HF/SSB antennas require a high standard of installation to work correctly.
- The ground system is a key part of the overall antenna system. A poor ground system is the most common reason for poor antenna performance.
- It is extremely important that the antenna location and grounding system are correctly chosen so that the system will radiate effectively.
- The longest possible antenna should be chosen for each installation.

- An unloaded whip antenna for use in the frequency range 2 - 30MHz.
- The radiating element is wholly enclosed inside the Radome.
- Suitable for both marine and land-based HF/SSB installations which include an antenna tuner
- A two section antenna, UPS shippable. The longest section is 2.45m long.
- The antenna gradually tapers to an outside diameter of 7mm at the top.
- UltraGlass stands up to high UV and harsh marine environments for years
- All ferrules and couplers are stainless steel.
- The stainless steel mount for this antenna can be side or deck mounted
- The polypropylene support bracket should be mounted approximately 900mm up from the base of the antenna (marked on the antenna Radome)

	P2031
Frequency Range	2 - 30MHz
Radome	UltraGlass
Ferrule and Couplers	Stainless Steel
Antenna Type	Whip
Polarisation	Vertical
Radiation Pattern	Omnidirectional
Power Rating	1kw PEP
Antenna Connection	5mm plated brass bolt 200mm above base
Height / Weight	4.9m/1.3kg
Bottom Section Diameter	40mm
Maximum Input (watts)	1000
Antenna Conductor	Full length (no loading)



P2031

15.01.07



PACIFIC AERIALS

169 Moore Street Howick
PO Box 38 421 Howick
Auckland New Zealand

PHONE: +64-9-533 5922
EMAIL: info@pacificaerials.com
WEB: www.pacificaerials.com

FAX: +64-9-533 5944
FREEFAX NZ: 0800- 677 688
FREEFAX AUST: 1800- 677 688