

VX-1700

HF Multi Mode Mobile Radio



- Frequency Coverage :
Rx: 30 kHz ~ 30.0000 MHz in 10 Hz Steps
Tx: 1.600 ~ 30.0000 MHz
- A1A (CW), J3E (LSB/USB), A3E (AM), J2B (USB/LSB), H3E (2.182 MHz Emergency Channel only)
- 200 Memory Channels (arranged in five banks)
- Alpha-Numeric labeling of Memory channels
- VFO mode capability
- ITU Marine Channel installed
- One touch 2.182 MHz Emergency Channel mode
- Power Output:
125 Watts (A1A, J2B, J3E @1.6000 ~ 3.9999 MHz)
100 Watts (A1A, J2B, J3E @4.0000 ~ 29.9999 MHz)
31 Watts AM Carrier (A3E @1.6000 ~ 3.9999 MHz)
25 Watts AM Carrier (A3E @4.0000 ~ 29.9999 MHz)
31 Watts AM Carrier (H3E @2.182 MHz)
- Weather resistant, Rugged Construction
- Mobile Antenna (Optional)
- Selcall / Telcall built in
Selcall
Telcall
Message Call
Position Request call
Position Send Call
Beacon Request Call
- ALE Operation (requires optional ALE-1 unit)
- Dual Watch Operation
- External Automatic Antenna Tuner, FC-30 and FC-40 available
- VOX
- Noise Blanker
- Dimmer function
- CW Side tone function
- CW Semi-break-in
- Transcript SSB Encryption Unit SC20-455 Available (Optional)
- Field Memory Channel Storage
- PC Programmable



VX-1700 HF Multi Mode Mobile Radio

Specifications

General Specifications	
Receiver Frequency Range	30 kHz ~ 30.0000 MHz
Transmitter Frequency	1.600 ~ 30.0000 MHz
Emission Modes	A1A (CW), J3E (LSB/USB), A3E (AM), J2B (USB/LSB), H3E (2.182 MHz Emergency Channel only)
Frequency Synthesizer Step	10 Hz, 100 Hz, 1 kHz
Frequency Stability	±4 ppm (after 1 min. ~ 60 min. @25° C) ±1 ppm (after 60 min. ~ @25° C)
Operating Temperature Range	14° F ~ 122° F (-10° C ~ +50° C)
Antenna Impedance	50 Ohms
Supply Voltage	13.8 Volts DC ±15%, negative ground
Power Consumption	Standby 25 mA Receive, no signal 1.0 A Receive 1.5 A Transmit 20 A (125 Watts output)
Dimensions (WxHxD)	9.5 x 3.9 x 11.2 (241 x 99 x 285 mm)
Weight (approx.)	9.5 lbs (4.3 kg)
Receiver Specifications	
Intermediate Frequencies	1st: 45.274 MHz, 2nd: 24 kHz
Sensitivity (A1A/J2B/J3E/A3E: S/N 10 dB)	A1A/J2B/J3E A3E/H3E
0.1 ~ 0.5 MHz	— —
0.5 ~ 1.6 MHz:	1.41 µV 8 µV
1.6 ~ 30 MHz:	0.16 µV 1 µV
Squelch Sensitivity (A1A/J2B/J3E)	0.1 ~ 0.5 MHz: — 0.5 ~ 1.6 MHz: 2.5 µV 1.6 ~ 30 MHz: 2 µV
IF Rejection	Better than 80 dB
Image Rejection	Better than 80 dB
Selectivity	—6 dB —60 dB
A1A(W), J2B(W), J3E	> 2.2 kHz < 4.5 kHz
A1A(N), J2B(N)	> 500 Hz < 2.0 kHz
A3E, H3E	> 6 kHz < 20 kHz
Audio Output	At least 2.2 Watts into 8 Ohms @ 10% THD
Audio Output Impedance	4 ~ 16 Ohms (8 Ohms Nominal)
Conducted Radiation	Less than 4000 µµW
Transmitter Specifications	
Power Output	125 Watts (A1A, J2B, J3E @ 1.6000 ~ 3.9999 MHz) 100 Watts (A1A, J2B, J3E @ 4.0000 ~ 29.9999 MHz) 31 Watts AM Carrier (A3E @ 1.6000 ~ 3.9999 MHz) 25 Watts AM Carrier (A3E @ 4.0000 ~ 29.9999 MHz) 31 Watts AM Carrier (H3E @ 2.182 MHz)
Modulation Types	J3E, H3E: PSN type modulator, A3E: Low-level (early stage)
Spurious Radiation	Better than -42 dB (Harmonics) Better than -36 dB (Harmonics @ 1.6 ~ 1.8 MHz)
J3E Carrier Suppression	Better than 50 dB below peak output
Undesired Sideband Suppression	Better than 60 dB below peak output
J3E Audio Response	Not more than -6 dB from 400 Hz ~ 2500 Hz
Occupied Bandwidth	A1A: less than 0.5 kHz J3E, H3E: less than 3.0 kHz A3E: less than 6.0 kHz
Microphone Impedance	200 ~ 10 k Ohms (600 Ohms Nominal)

Specifications are subject to change without notice or obligation.

Rear Panel



Vertex Standard

Nabishi Systems

Nabishi UK Ltd
16c Upton Road,
Tilehurst, Reading, Berks,
RG30 4BJ, England,
United Kingdom.
Tele +44 (0) 118 943 3311
Fax +44 (0) 118 943 3366

Accessories & Options



VL-1000 Linear Amplifier /
VP-1000 AC Power Supply for the VL-1000



FP-1030A AC Power Supply



MD-200A8X
Desktop Microphone



FC-40
External Antenna Tuner (Wire/Whip Antennas)



FC-30
External Antenna Tuner (Coaxial Lines)



MLS-100
External Speaker

- ALE-1 Automatic Link Establishment Unit
- SC20-455 Encryption Unit
- YA-30 Broadband HF Antenna
- YA-007FG HF Multi-Band Mobile Antenna for FC-40
- MMB-89 One-Touch Mobile Bracket
- MHG-1 Carrying Handle
- CT-118 Linear Amplifier Control Cable
- CE77 PC programmer

Various accessories listed may not be available in some countries.

ISO9001:2000



YAESU MUSEN CO., LTD
ISO9001:2000 certification

ISO14001:1996



YAESU MUSEN CO., LTD
ISO14001:1996 certification